

# Wall mounted unit

FTXTP-M + RXTP-R



**BLUEEVOLUTION** comfora



Guaranteed operation down to -25°C



Daikin Residential Controller



Energy saving during standby mode



3-D air flow

Wall mounted unit providing high efficiency and comfort down to -25°C

- › Guaranteed heating capacity down to -25°C
- › Ideal for above door installation
- › Full range A++
- › Daikin residential controller via app
- › Voice control
- › Space saving contemporary wall mounted design
- › Bluevolution range: lower environmental impact
- › 3-D airflow: air is blown into all corners of a room

# FTXTP-M + RXTP-R



Indoor unit		FTXTP		25M	35M
Dimensions	Unit	HeightxWidthxDepth	mm	286 x770 x225	
Weight	Unit		kg	9.00	
Air filter	Type			Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/Low/ Medium/High	m <sup>3</sup> /min 3.9 /5.5 /8.3 /11.5	
		Heating	Silent operation / Low / Medium / High	m <sup>3</sup> /min 4.5 / 5.6 / 8.7 / 11.5	
Sound power level	Cooling		dBA	58	
	Heating		dBA	58	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	21 /26 /43	
	Heating	Silent operation/Low/High	dBA	21 /26 /43	
Control systems	Infrared remote control			ARC480A53	
	Wired remote control			BRC944B2 / BRC073A1	

Cooling: indoor temp. 27°CDB, 19.0°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data


Outdoor unit		RXTP		25R	35R
Dimensions	Unit	HeightxWidthxDepth	mm	551 x763 x312	
Weight	Unit		kg	38	
Sound power level	Cooling		dBA	61	
Sound pressure level	Cooling	Nom.	dBA	48	
	Heating	Nom.	dBA	49	
Operation range	Cooling	Ambient	Min.~Max.	°CDB -10 ~46	
	Heating	Ambient	Min.~Max.	°CWB -25 ~18	
Refrigerant	Type			R-32	
	GWP			675	
	Charge		kg/TCO <sub>2</sub> Eq	1.1 /-	
Piping connections	Liquid	OD	mm	6.35	
	Gas	OD	mm	9.50	
	Piping length	OU - IU	Max.	m 20	
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m 15	
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240	
	Current - 50Hz	Maximum fuse amps (MFA)	A	16	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTP + RXTP		25M + 25R	35M + 35R
Cooling capacity	Min./Nom./Max.		kW	0.80 /2.50 /4.00	0.80 /3.50 /4.40
Heating capacity	Min./Nom./Max.		kW	1.20 /3.20 /6.20	1.20 /4.00 /6.70
Power input	Cooling	Nom.	kW	0.57	0.92
	Heating	Nom.	kW	0.65	0.90
Space cooling	Energy efficiency class			A++	
	Capacity	Pdesign	kW	2.50	3.50
	SEER			7.10	7.20
	Annual energy consumption		kWh/a	123	170
Space heating (Average climate)	Energy efficiency class			A++	
	Capacity	Pdesign	kW	2.50	3.00
	SCOP/A			4.93	4.81
	Annual energy consumption		kWh/a	710	873
Space heating (Cold climate)	Energy efficiency class			A	
	Capacity	Pdesign	kW	3.65	4.38
	Annual energy consumption		kWh/a	1,941	2,394
	SCOP/C			3.95	3.84
Nominal efficiency	EER			4.40	3.80
	COP			4.95	4.44
	Annual energy consumption		kWh	284	461
	Energy labeling Directive	Cooling/Heating		A/A	

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN21-065

06/2021



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.