

# Wall mounted unit

FTXTP-N + RXTP-A



BLUEEVOLUTION nepura comfora



Guaranteed operation down to -30°C



Energy saving during standby mode



3-D air flow

Wall mounted unit providing high efficiency and comfort down to -30°C

- › Guaranteed heating capacity down to -30°C
- › Ideal for above door installation
- › Full range A++
- › 3-D airflow: air is blown into all corners of a room
- › Onecta app

- › Voice control
- › Space saving contemporary wall mounted design
- › Bluevolution range: lower environmental impact

# FTXTP-N + RXTP-A



Indoor unit			FTXTP	25N	35N
Dimensions	Unit	HeightxWidthxDepth	mm	286 x770 x225	
Weight	Unit		kg	9	
Air filter	Type			Removable / washable	
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m <sup>3</sup> /min	
		Heating	Silent operation / Low / Medium / High	m <sup>3</sup> /min	
Sound power level	Cooling		dB(A)	58.0	
	Heating		dB(A)	58.0	
Sound pressure level	Cooling	Silent operation/Low/High	dB(A)	21.0 /26.0 /43.0	
	Heating	Silent operation/Low/High	dB(A)	21.0 /26.0 /43.0	
Control systems	Infrared remote control			ARC480A53	
	Wired remote control			BRC073A1	

Cooling: indoor temp. 27°CDB; 19°CWB; outdoor temp. 35°CDB; 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB; 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit			RXTP	25A	35A
Dimensions	Unit	HeightxWidthxDepth	mm	605 x930 x376	
Weight	Unit		kg	42	
Sound power level	Cooling		dB(A)	60	
	Heating		dB(A)	60	
Sound pressure level	Cooling	Nom.	dB(A)	48.0	
	Heating	Nom.	dB(A)	49.0	
Operation range	Cooling	Ambient	Min.-Max.	°CDB	
	Heating	Ambient	Min.-Max.	°CWB	
Refrigerant	Type			R-32	
	GWP			675.0	
	Charge		kg/TCO <sub>2</sub> Eq	0.97 /0.66	
Piping connections	Liquid	OD	mm	6.35	
	Gas	OD	mm	9.50	
	Piping length	OU - IU	Max.	m	
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)	
Power supply	Level difference		IU - OU	Max.	
	Phase/Frequency/Voltage		Hz/V	1~/50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)		A	16	

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data			FTXTP + RXTP	25N + 25A	35N + 35A
Cooling capacity	Min./Nom./Max.		kW	1.0/2.5/4.1	1.0/3.5/4.5
Heating capacity	Min./Nom./Max.		kW	1.0/3.2/6.20	1.0/4.0/6.70
Power input	Cooling	Nom.	kW	0.52	0.79
	Heating	Nom.	kW	0.65	0.88
Space cooling	Energy efficiency class			A+++	
	Capacity	Pdesign	kW	2.50	3.50
	SEER			8.55	8.51
	Annual energy consumption		kWh/a	102	144
Space heating (Average climate)	Energy efficiency class			A++	
	Capacity	Pdesign	kW	2.50	3.00
	SCOP/A			4.95	4.85
	Annual energy consumption		kWh/a	707	866
Space heating (Cold climate)	Energy efficiency class			A	
	Capacity	Pdesignh	kW	3.65	4.38
	Annual energy consumption		kWh/a	1,937	2,426
	SCOP/C			3.96	3.79
Nominal efficiency	EER			4.88	4.45
	COP			4.95	4.55
	Annual energy consumption		kWh	260	395
	Energy labeling Directive	Cooling/Heating		A/A	
Current - 50Hz	Maximum fuse amps (MFA)		A	16	

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

ECPEN23-065 08/2023

