Wall mounted unit

ATXTM-A + ARXTM-A



Siesta

Weather compensation function

Guaranteed operation down to -30°C

Fireplace logic

Heat boost

Onecta app

Attractive, wall mounted Siesta unit with perfect indoor air quality

› Guaranteed heating operation down to -30°C
› Keeps properties warm inside when outdoor temperatures drop
› Comfort+: perfect comfort with homogeneous temperature
› Seasonal efficiency values up to A+++ in cooling and heating
› Even temperature distribution thanks to fire place logic
› Heat boost: fast heating during start-up (pair only)
› 2 area motion detection sensor
› Purifies the air of viruses, bacteria, fine dust, odours, allergens, etc
› Daikin Flash Streamer technology: powerful air purification
› Silver allergen removal and air purifying filter
› Voice control
› Onecta app
› Quiet in operation: down to 19dBA sound pressure level
› 3-D airflow: air is blown into all corners of a room

ATXTM-A + ARXTM-A



Efficiency data				ATXTM + ARXTM	30A + 30A
Cooling capacity	Min./Nom./Max.			kW	1.2 /3 /4.6
Heating capacity	Min./Nom./Max.			kW	0.8 /3.2 /7.4
Power input	Cooling		Nom.	kW	0.58
	Heating		Nom.	kW	0.6
Space cooling	Energy efficiency class				A+++
	Capacity		Pdesign	kW	3
	SEER				8.65
	Annual energy consumption			kWh/a	121
Space heating (Average climate)	Energy efficiency class				A+++
	Capacity		Pdesign	kW	3
	SCOP/A				5.35
	Annual energy consumption			kWh/a	785
Space heating (Cold climate)	Energy efficiency class				A+
	Capacity		Pdesignh	kW	4.38
	Annual energy consumption			kWh/a	2,176
	SCOP/C				4.23
Nominal efficiency	EER				5.13
	COP				5.3
	Annual energy consumption			kWh	292
	Energy labeling Directive		Cooling/Heating		A/A
Current - 50Hz	Maximum fuse amps (MFA)			A	16

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Indoor unit				ATXTM	30A
Dimensions	Unit	HeightxWidthxDepth		mm	298 x804 x252
Weight	Unit			kg	12
Air filter	Type				Removable / washable
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m^3/min	4.8 /5.6 /8.1 /13.2
		Heating	Silent operation / Low / Medium / High	m^3/min	4.7 / 5.6 / 7.7 / 11.7
Sound power level	Cooling			dBA	60
	Heating			dBA	59
Sound pressure level	Cooling	Silent operation/Low/High		dBA	21 /25 /45
	Heating	Silent operation/Low/High		dBA	19 /22 /43
Control systems	Infrared remote control				ARC466A83
	Wired remote control				-

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit				ARXTM	30A
Dimensions	Unit	HeightxWidthxDepth		mm	605 x930 x376
Weight	Unit			kg	42
Sound power level	Cooling	Nom.		dBA	60
	Heating	Nom.		dBA	60
Sound pressure level	Cooling	Nom.		dBA	48
	Heating	Nom.		dBA	49
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~46
	Heating	Ambient	Min.~Max.	°CWB	-31 ~18
				°CDB	-30 ~24
Refrigerant	Type				R-32
	GWP				675
	Charge			kg/ tCO2Eq	0.97 /0.66
Piping connections	Liquid	OD		mm	6.35
	Gas	OD		mm	9.5
	Piping length	OU - IU	Max.	m	20
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m	15
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240
Current - 50Hz	Maximum fuse amps (MFA)			A	16

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende

ECPEN24-066 10/2024

Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.